



**CITY OF ESSEX JUNCTION
BIKE WALK ADVISORY COMMITTEE
REGULAR MEETING AGENDA**

Online & 6 Lincoln St. (Kolvoord Room)
Essex Junction, VT 05452
Tuesday, October 22th
2024, 7:00 PM

E-mail: mgiguere@essexjunction.org

www.essexjunction.org

Phone: 802-878-6944, ext. 1625

This meeting will be held in-person at 6 Lincoln Street in the Kolvoord Room at Brownell Library and available remotely. Options to join the meeting remotely:

- **JOIN ONLINE:** [Join Zoom Meeting](#)
- **JOIN CALLING:** (toll free audio only): (888) 788-0099 | Meeting ID: 958-5750-2850; Passcode: 790174

1. **CALL TO ORDER** [7:00 PM]
2. **DETERMINE WHO WILL TAKE MINUTES**
3. **AGENDA ADDITIONS/CHANGES**
4. **MINUTES FOR APPROVAL**
 - a. September 24th, 2024
5. **PUBLIC TO BE HEARD**
6. **BUSINESS ITEMS**
 - a. RRFB location consideration
 - b. Bike parking survey data
7. **MEMBERS UPDATES**
8. **STAFF UPDATES**
 - a. CCRPC Bike/Ped data updates
 - b. Bike locker updates
 - c. Connect the Junction recap
 - d. CATMA Summit recap
9. **READING FILE**
 - a. RRFB Applications and Considerations
10. **ADJOURN**

This agenda is available in alternative formats upon request. Meetings of the Planning Commission, like all programs and activities of the City of Essex Junction, are accessible to people with disabilities. For information on accessibility or this agenda, call the City Manager's office at 802-878-6944 TTY: 7-1-1 or (800) 253-0191.



Safety Benefits:

RRFBs can reduce crashes up to:

47%

for pedestrian crashes.⁴

RRFBs can increase motorist yielding rates up to:

98%

(varies by speed limit, number of lanes, crossing distance, and time of day).³



RRFBs used at a trail crossing.
Source: LJB

For more information on this and other FHWA Proven Safety Countermeasures, please visit <https://highways.dot.gov/safety/proven-safety-countermeasures> and https://highways.dot.gov/sites/fhwa.dot.gov/files/2022-06/techSheet_RRFB_2018.pdf.

Rectangular Rapid Flashing Beacons (RRFB)

A marked crosswalk or pedestrian warning sign can improve safety for pedestrians crossing the road, but at times may not be sufficient for drivers to visibly locate crossing locations and yield to pedestrians. To enhance pedestrian conspicuity and increase driver awareness at uncontrolled, marked crosswalks, transportation agencies can install a pedestrian actuated Rectangular Rapid Flashing Beacon (RRFB) to accompany a pedestrian warning sign. RRFBs consist of two, rectangular-shaped yellow indications, each with a light-emitting diode (LED)-array-based light source.¹ RRFBs flash with an alternating high frequency when activated to enhance conspicuity of pedestrians at the crossing to drivers.

Transportation agencies should refer to the *Manual on Uniform Traffic Control Devices (MUTCD)* for information on the application of RRFBs.¹

Applications

The RRFB is applicable to many types of pedestrian crossings but is particularly effective at multilane crossings with speed limits less than 40 miles per hour.² Research suggests RRFBs can result in motorist yielding rates as high as 98 percent at marked crosswalks, but varies depending on the location, posted speed limit, pedestrian crossing distance, one- versus two-way road, and the number of travel lanes.³ RRFBs can also accompany school or trail crossing warning signs.

RRFBs are placed on both sides of a crosswalk below the pedestrian crossing sign and above the diagonal downward arrow plaque pointing at the crossing.¹ The flashing pattern can be activated with pushbuttons or passive (e.g., video or infrared) pedestrian detection, and should be unlit when not activated.

Considerations

Agencies should:²

- Install RRFBs in the median rather than the far-side of the roadway if there is a pedestrian refuge or other type of median.
- Use solar-power panels to eliminate the need for a power source.
- Reserve the use of RRFBs for locations with significant pedestrian safety issues, as over-use of RRFB treatments may diminish their effectiveness.

Agencies shall not:²

- Use RRFBs without the presence of a pedestrian, school or trail crossing warning sign.
- Use RRFBs for crosswalks across approaches controlled by YIELD signs, STOP signs, traffic control signals, or pedestrian hybrid beacons, except for the approach or egress from a roundabout.

¹ Manual on Uniform Traffic Control Devices (MUTCD), Chapter 4L. FHWA, (2023).

² "Rectangular Rapid Flash Beacon" in PEDSAFE: Pedestrian Safety Guide and Countermeasure Selection System. FHWA, (2013).

³ Fitzpatrick et al. "Will You Stop for Me? Roadway Design and Traffic Control Device Influences on Drivers Yielding to Pedestrians in a Crosswalk with a Rectangular Rapid-Flashing Beacon." Report No. TTI-CTS-0010. Texas A&M Transportation Institute, (2016).

⁴ (CMF ID: 9024) NCHRP Research Report 841 Development of Crash Modification Factors for Uncontrolled Pedestrian Crossing Treatments, (2017).